



FEATURES

- Wide operating voltage:
 - 42V ~ 57V
- 802.3bt interface built-in
- Active bridge to reduce power loss
- Output Current:
 - 5V, 14A
 - 12V, 6A
 - 28V, 2.6A
- Output voltage ripple: 120 mVpp (input 48V, [12V@6A](#))
- High Efficiency 90.5% (input 48V, [12V@6A](#) including bridge)
- Output Voltage adjust: 90% to 110% of $V_{O,SET}$
- Overcurrent/short-circuit protection
- Supports Ultra-Low Power Standby Modes
- High reliability: designed to meet 500k hour MTBF
- Minimal space on PCB:
 - 58.42 mm x 22.86 mm x 10.5 mm
 - 2.3 in x 0.9 in x 0.41 in
- No derating to +TBD°C, natural convection
- Design to meet UL/IEC/EN60950
- Operating Temperature: -40 ~ +85°C

APPLICATIONS

- IP Camera & Tilt
- Wireless Access Point
- Video Supervisory
- Remote BBU

Description



The **POE MQ7804bt/ MQ7814bt** series of modules are designed to extract power from a conventional twisted pair Category 5 Ethernet cable, conforming to the IEEE 802.3bt Power-over-Ethernet (PoE) standard but with 72W output power. The MQ7804bt series of modules embedded 2 active rectifier bridges which extremely reduce the power dissipation comparing with the traditional Schottky diodes bridges, have two pairs of power inputs pins: - VA1&2 and VB1&2 to accommodate high power PoE application with 4-pair wire power transfer.

In some applications, the input polarity is certain, or there is an external rectifier bridge, the MQ7814bt series modules are more cost effective options; compare with MQ7804bt series, MQ7814bt series products have exactly the same performance except the embedded 2 active rectifier bridges removed.

The **MQ7804bt/ MQ7814bt** signature and control circuit provides the PoE bt compatibility signature and power classification required by the Power Sourcing Equipment (PSE) before applying up to power to the port. The **MQ7804bt/ MQ7814bt** can be set to class4 to class 8 by external one classification resistor to get different power class from PSE.

The high efficiency DC/DC converter operates over a wide input voltage range and provides a regulated low ripple and low noise output. The DC/DC converter also has built-in overload and short-circuit output protection.

***** Typical Application Circuit *****



MQ7814bt application diagram, with external rectifier bridges

Note:


C_{IN} recommended from 47μF to 220μF AL-cap with 5~10μF ceramic cap;

Performance Specifications (at $T_a=+25^\circ\text{C}$)

Model	Input V_{IN} Range (V)	Output				Efficiency (%)	
		$I_{OUT,MAX}$ (A)	V_{out} (V)	Regulation			
				Line (%)	Load (%)		
MQ7804BTT050	42 ~57	14	5	0.5	0.5	TBD	
MQ7804BTT120		6.0	12	0.5	0.5	90.5	
MQ7804BTT280		2.6	28	0.5	0.5	TBD	
MQ7814BTT050		14	5	0.5	0.5	TBD	
MQ7814BTT120		6.0	12	0.5	0.5	91.4	
MQ7814BTT280		2.6	28	0.5	0.5	TBD	

Mechanical Specifications

Dimensions are in millimeters (inches)



BOT View

Side View

PIN	MQ7804BT		MQ7814BT
	DESCRIPTION		
1	VIN+	PoE positive input	
2	VIN-	PoE negative input	
3	RCLS1	classification resistor #1	
4	RCLS2	classification resistor #2	
5	VNEG	Bridge negative output	N/C
6	VPOS	Bridge positive output	
7	VA1	Pair from network transformer's central tap	N/A
8	VA2		
9	VB1		
10	VB2		
11, 12, 13	Vo-	Output negative end	
14	Trim	Output Trim	
15, 16, 17	Vo+	Output positive end	
18	VDC+	DC/DC positive input end	
19	VDC-	DC/DC negative input end	

Ordering Information

MQ7804BTT120-TP

Union P/N#				TP:With Heat Sinks
MQ7804:With rectifier bridge				Output Voltage: 120 for 12V
MQ7814:Without rectifier bridge				T: Through Hole
BT: 802.3bt standard				

Absolute Maximum Ratings

Note: These are stress ratings. Exposure of devices to any of these conditions may adversely affect long-term reliability. Proper operation under conditions other than those listed in the Performance Specifications Table is not implied.

Parameter	Symbol	Min	Max	Unit
Operating Ambient Temperature	T_A	-40	85	°C
Storage Temperature	T_{STG}	-40	85	°C
Altitude			4000	m
I/O Isolation voltage (100% factory Hi-pot tested)			2250	V _{DC}

MQ7804BT/MQ7814BT General Specifications: ($T_A=+25^\circ\text{C}$)

Note: Unless otherwise indicated, specifications apply over all operating input voltage, resistive load, and temperature conditions.

Parameter	Condition	Symbol	Min	Typ.	Max	Unit
Operating Input Voltage Range	100% Load	V_{IN}	42		57	V _{DC}
V_{IN} - Inrush current limit	$(V_{DC}-) - (V_{IN}) > 2 \text{ V}$, During C_{IN} charge period		275	335	395	mA
Input Current Limit	$V_{IN}=V_{IN.\text{MIN}}$ To $V_{IN.\text{MAX}}$		1.9	2.2	2.5	A
Input Turn-ON Threshold	10% Max Load, input rising	$V_{IN.\text{ONTH}}$	40.5		41.5	V _{DC}
Input Turn-OFF Threshold	10% Max Load, input falling	$V_{IN.\text{OFFTH}}$	38.3		39.3	V _{DC}
Output Power	$V_{IN}=V_{IN.\text{MIN}}$ To $V_{IN.\text{MAX}}$	P_o	0		72	W
Output Continuous Short-circuit Protection	$V_{IN}=V_{IN.\text{MIN}}$ To $V_{IN.\text{MAX}}$			YES		
Over Temperature	Hiccup Auto Restart			125		°C
MTBF			500,000			Hours

MQ7804BTT050 Electrical Specifications: ($T_A=+25^\circ\text{C}$)

Parameter	Condition	Symbol	Min	Typ.	Max	Unit
Input No Load Current	$V_{IN}=48\text{V}$, $V_o=V_{O.\text{SET}}$, $I_o=0$, module enabled	$I_{IN.\text{NOLOAD}}$				mA
Nominal Output Voltage Set-point	$V_{IN} = V_{IN.\text{MIN}}$ To $V_{IN.\text{MAX}}$			5		V
Maximum load	$V_{IN} = V_{IN.\text{MIN}}$ To $V_{IN.\text{MAX}}$				14.4	A
Output Voltage Set point	100% load	ΔV_o	-1		+1	% $V_{O.\text{SET}}$
Adjustment Range		$V_{O.\text{ADJ}}$	-10		10	% $V_{O.\text{SET}}$
Output Ripple and Noise Voltage	$V_{IN}=48\text{V}$ $I_o=10\text{A}$, 5~20MHz, Measured with $0.1\mu\text{F}$ ceramic					mVpp

POE input power module, MQ7804bt/ MQ7814bt

Transient Response	Load step from 50%~100%~50% $I_{O,MAX}$, $di/dt=0.1A/\mu S$					mV
	Response time					μS
Efficiency	$V_{IN}=48$, 100% Load, including bridge	η				%
	$V_{IN}=48$, 100% Load, no bridge	η				%
Switching Frequency		F_O				KHz
External Capacitive Load		$C_{O,EXTERNAL}$				μF
Inrush Current	$V_{IN}=55V$	I_{inrush}				mA


MQ7804BTT120 Electrical Specifications: ($TA=+25^\circ C$)

Parameter	Condition	Symbol	Min	Typ.	Max	Unit
Input No Load Current	$V_{IN}=48V$, $V_o=V_{o,SET}$, $I_o=0$, module enabled	$I_{IN,NOLOAD}$		70		mA
Nominal Output Voltage Set-point	$V_{IN} = V_{IN,MIN}$ To $V_{IN,MAX}$			12		V
Maximum load	$V_{IN} = V_{IN,MIN}$ To $V_{IN,MAX}$				6	A
Output Voltage Set point	100% load	ΔV_o	-1		+1	% $V_{o,SET}$
Adjustment Range		$V_{o, ADJ}$	-10		10	% $V_{o,SET}$
Output Ripple and Noise Voltage	$V_{IN}=48V$ $I_o=4.2A$, 5~20MHz, Measured with 0.1 μF ceramic			120		mVpp
Transient Response	Load step from 50%~100%~50% $I_{O,MAX}$, $di/dt=0.1A/\mu S$			100		mV
	Response time			350		μS
Efficiency	$V_{IN}=48$, 100% Load, including bridge	η	89.5	90.5		%
	$V_{IN}=48$, 100% Load, no bridge	η	90.4	91.4		%
Switching Frequency		F_O		400		KHz
External Capacitive Load		$C_{O,EXTERNAL}$	0		2000	μF
Inrush Current	$V_{IN}=55V$	I_{inrush}		150		mA


MQ7804BTT280 Electrical Specifications: ($TA=+25^\circ C$)

Parameter	Condition	Symbol	Min	Typ.	Max	Unit
Input No Load Current	$V_{IN}=48V$, $V_o=V_{o,SET}$, $I_o=0$, module enabled	$I_{IN,NOLOAD}$				mA
Nominal Output Voltage Set-point	$V_{IN} = V_{IN,MIN}$ To $V_{IN,MAX}$			28		V
Maximum load	$V_{IN} = V_{IN,MIN}$ To $V_{IN,MAX}$				2.8	A
Output Voltage Set point	100% load	ΔV_o	-1		+1	% $V_{o,SET}$
Adjustment Range		$V_{o, ADJ}$	-10		10	% $V_{o,SET}$
Output Ripple and Noise Voltage	$V_{IN}=48V$ $I_o=2.1A$, 5~20MHz, Measured with 0.1 μF ceramic					mVpp
Transient Response	Load step from 50%~100%~50% $I_{O,MAX}$, $di/dt=0.1A/\mu S$					mV
	Response time					μS
Efficiency	$V_{IN}=48$, 100% Load, including bridge	η				%
	$V_{IN}=48$, 100% Load, no bridge	η				%
Switching Frequency		F_O				KHz
External Capacitive Load		$C_{O,EXTERNAL}$				μF
Inrush Current	$V_{IN}=55V$	I_{inrush}				mA

Test Configurations



NOTE: Class Resistor Selection
Fig 1. Classification Resistors



NOTE: Trimming function is allowed the output voltage set point to be adjusted from the default value in a allowed range.

Fig 2. Output Trim

Output Trim

MQ7804B output can be trimmed up or down by connecting one resistor to output negative or positive end as **Fig 2. Output Trim**. Connecting an external resistor (R_{DN}) between the TRIM pin and the $V_{O(-)}$ (or Sense(-)) pin decreases the output voltage set point. To maintain set point accuracy, the trim resistor tolerance should be $\pm 1.0\%$. The following equation determines the required external resistor value:

$$R_{DN} = \left(\frac{5.11 * V_{O,SET}}{V_{O,SET} - V_{O,DN}} - 10.22 \right) K\Omega$$

$V_{O,SET}$ is the output default set-point voltage of the module, $V_{O,DN}$ is the desired trim-down output voltage. Connecting an external resistor (R_{UP}) between the TRIM pin and the $V_{O(+)}$ (or Sense (+)) pin increases the output voltage set point. The following equation determines the required external resistor value:

$$R_{UP} = \left[\frac{5.11 * V_{O,SET}}{V_{O,UP} - V_{O,SET}} * \left(\frac{V_{O,UP}}{1.225} - 1 \right) - 10.22 \right] K\Omega$$

$V_{O,SET}$ is the output default set-point voltage of the module, $V_{O,UP}$ is the desired trim-up output voltage.

Over-temperature Protection

To provide protection under certain fault conditions, the unit is equipped with a thermal shutdown circuit. The unit will shutdown if the thermal reference points, T_{ref} , exceed $125^\circ C$ respectively, but the thermal shutdown is not intended as a guarantee that the unit will survive temperatures beyond its rating. The module will automatically restart upon cool-down to a safe temperature.

Classification Resistors

Connect a resistor from RCLS to VIN- to program the classification current according to the IEEE 802.3bt standard. Table 1 lists the external resistor values required for each of the PD power ranges defined by IEEE802.3bt.

PD class	Power at PD(W)	$R_{CLS1}(\Omega)$	$R_{CLS2}(\Omega)$
4	25.5	63.4	N/A
5	40	1210	2000
6	51	249	150
7	62	140	80.6
8	71	90.9	51.1

Table 1. Class Resistor Selection

Current limit during startup


IEEE 802.3bt has a startup current limitation, providing compatibility between a PSE of any Type and a PD of any Type. When input voltage rises above input Turn-ON Threshold (VIN.ONTH), the **MQ7804bt/ MQ7814bt** starts charging the bulk capacitor CIN under the 335mA VIN- inrush current limit, which is compatible with all PSE type. Once the inrush current falls about 10% below the inrush current limit, the **MQ7804bt/ MQ7814bt** internal current limit switches to the operational level, which is approximately 2.2 A, and internal DCDC converter will be started shortly.

Typical Characteristics – MQ7804BTT120


General conditions:

Input filter 100 μ F/100V AL-Cap;


Output filter 0.1 μ F/50V Ceramic Cap;




Noise & Ripple $V_{IN}=42V$, $I_o=6A$, 5~20MHz Bandwidth




Noise & Ripple $V_{IN}=48V$, $I_o=6A$, 5~20MHz Bandwidth




Noise & Ripple $V_{IN}=57V$, $I_o=6A$, 5~20MHz Bandwidth









Transient Response, $V_{IN}=42V$ 3A~6A~3A load step
Red: Load Current Yellow: Output Voltage




Transient Response, $V_{IN}=48V$ 3A~6A~3A load step
Red: Load Current Yellow: Output Voltage




Transient Response, $V_{IN}=57V$ 3A~6A~3A load step
Red: Load Current Yellow: Output Voltage






Power Dissipation



No Wind Derating
Inside the box size:36cm*26cm*10cm



Cold Plate Derating
Aluminum plate size: 270mm*165mm*10mm

Recommended Hole Pattern

Dimensions are in millimeters (inches)

